

We see what you can't. The future of flame detection is here.

Multi Spectrum IR H₂ Flame Detector

FDS303H

Designed for hazardous industries where fast H₂ flame detection is critical and nuisance alarms are not an option.

The MICROPACK FDS303H is an explosion proof Multi Spectrum IR hydrogen (H₂) flame detector. The device delivers superior performance, responding to hydrogen fires at long distances.

The FDS303H has been independently tested to demonstrate it can detect a hydrogen plume fire at 40m (131ft) in 5 seconds.



Description

Multi Spectrum IR H₂ Flame Detector

The FDS303H compliments the FDS series of Visual and IR3 Flame Detectors by delivering superior detection performance of hydrogen (H₂) fires. The FDS303H utilises the latest IR flame detection algorithms to ensure maximum false alarm immunity.

Applications

Typical applications include:

- Petroleum refining
- Semiconductor manufacturing
- Aerospace applications
- Fertilizer production
- Pharmaceuticals
- Hydrogen Compressors
- Hydrogen Fueling Stations
- Hydrogen Trains / Buses
- Hydrogen Ferries
- Hydrogen to Methane Production
- Refrigeration
- Gas Plants
- Hydrogen Generators

Features and Benefits

- Multi Spectrum IR design delivers long detection distances and enhanced false alarm immunity
- Continuous optical test
 - Verifies operation and improves device up-time
- Microprocessor controlled heated optics
 - Maintains operation in harsh weather conditions (snow, ice, condensation)
- International hazardous area approvals
 - FM / ATEX / IEC Ex / INMETRO* / PESO* / ECAS*
- Designed to meet performance testing to multiple fuels
 - FM 3260
 - EN 54-10
- Adjustable sensitivity levels
 - Application flexibility
 - Ensure detectors do not cross vote
- External testing with a long-range flame simulator
 - Minimizes the need for scaffolding
- External testing and calibration with a long range flame simulator
- Easy integration using industry standard outputs:
 - Configurable Alarm and Fault Relays
 - 0-20mA
 - HART®
- Certified SIL2 capable
- 5 year warranty

micropacksafety.com

Doc Ref: 3304.0002 Rev 0.3
Subject to modifications. © 2024 Micropack (Engineering) Ltd
ISO 9001:2015 Certified

Technical Specification

Environmental

Operating Temp: -76°F to +185°F (-60°C to +85°C)
Storage Temp: -76°F to +185°F (-60°C to +85°C)
Humidity: 0 to 93% RH non-condensing

Operating Voltage

24 Vdc Nominal – (Range 18 to 32 Vdc)

Power Consumption

3 W minimum (heater off)
12 W maximum (heater on)

Field of View

90° horizontal by 90° vertical

Flame Sensitivity

	Fuel	Fire Size	Distance
High sensitivity	Hydrogen	0.9m (36 inch) plume	40m (131 feet)
	Methylated Spirits	0.3m x 0.3m (1ft ²)	20m (65 feet)
	Methanol	0.3m x 0.3m (1ft ²)	20m (65 feet)
	n-Heptane	0.3m x 0.3m (1ft ²)	12m (40 feet)
	Methane	0.9m (36 inch) plume	30m (100 feet)

Speed of Response

~5 seconds (Typical) at 40 m (131 feet)

Enclosure

Dimensions: 4" Dia x 8" L (inches)
100 mm Dia x 200 mm

Material: Copper free aluminum
or 316 stainless steel

Entry size: 3/4 inch NPT or M25, Single or Dual

Weight: Aluminum 5.5 lbs (2.5 Kg)
Stainless steel 13.2 lbs (6 Kg)

Outputs

Configurable relay contacts (SPST 2A at 30Vdc) – alarm and fault.
0–20mA, HART®

Certification

FM approved
Class 1 Div 1, Groups B, C, D T4
Class 1 Zone 1 AEx/Ex db IIC T4
Ambient: -50°C to +85°C



ATEX II 2 G Ex db IIC T4
IECEx Ex db IIC T4
Ambient: -60°C to +85°C



INMETRO Ex db IIC T4*
PESO Ex db IIC T4*
Ta= -60°C to +85°C



*Pending

Performance approvals

FM 3260
EN 54-10



Ingress:

IP67 | NEMA type 6P

IEC 61508:

Certified SIL 2 Capable



Marine:

DNV GL Type Approval
ABS Product Assessment

Accessories

- Flame simulator (FS301)
- 2", 3" & 4" Pole mount bracket
- Retrofit mounting bracket
- Marine mounting bracket
- Sunshield
- Duct Mount Bracket
- Air Shield
- Detector Sealing Kit